

Ashcroft® Accessories - 2265 Electric Contacts

ELECTRIC WARNING CONTACTS

The Ashcroft® 2265 electric contact is an ideal accessory to turn on a signal light, sound an alarm, or operate a pump or valve. The contacts can easily be set so that a circuit can be closed or opened at a desired pressure or temperature.

Settings can be easily made in the field without removing the instrument from service. Contact adjustment is made externally with a removable key to make the instrument virtually tamper proof.

The contact is designed for easy installation on Types 1279, 1377 and 1379 Duragauge pressure gauges (either stem or flush mounted), Type 1125 differential pressure gauges, or Type 600A Duratemp dial thermometers.

Contacts are equipped with adjustable magnets to eliminate chatter caused by vibration. A plug-in connector with five feet of electrical cable is standard.

Use with Ashcroft Model No.	Description	Availability			
		Code		Mounting	
		45	60	Stem	Flush
		4½" Dial	6" Dial		
1279	Duragauge	X	—	X	X ⁽¹⁾
1377	pressure	X	X	—	X
1379	gauge	X	X	X	X ⁽¹⁾
1125	D/P gauge	X	X	X	X
				Surface	Flush
600A-02	Duratemp	X	X	—	X
600A-03	remote	X	X	X	X
600A-04	thermometer	X	X	X	X

⁽¹⁾ Flush mounting requires type 1278 flush mounting ring.
 All specifications are subject to change without notice.

Model	Code	Contact arrangements
2265	XED	High and low contact
	XEE	Double high contact
	XEF	Double low contact
	XEG	"OFF" at low and high, and "ON" in between



Indicating accuracy of Ashcroft Duragauge, above 300 psi with contact: Pointer not carrying contact – 1.0%.
 Pointer carrying contact – 1.5%. For ranges below 30 psi, add an additional ½% to indicating accuracies.