



RANGE DN	ØD1		ØG	H3	ØK	M
	≥ 0,6 bar	≤ 400 mbar				
DN20/PN40	[4,13] 105	[6,18] 157	[2,28] 58	[5,35] 136	[2,95] 75	4 x M12
DN25/PN40	[4,53] 115		[2,68] 68		[3,35] 85	
DN50/PN40	[6,50] 165	[6,50] 165	[4,02] 102	[2,00] 50,8	[4,92] 125	4 x M16
1" CL150	-	[4,25] 108			[5,75] 146	[3,12] 79,2
	[4,25] 108	-		[5,79] 147		
1" CL300	-	[4,88] 123,9		[5,94] 151	[3,50] 88,9	4 x 5/8-11 UNC
	[4,88] 123,9	-		[5,98] 152		
1 1/2" CL150	-	[4,92] 125,0		[5,83] 148	[3,87] 98,4	4 x 1/2-13 UNC
	[4,92] 125,0	-		[5,87] 149		
1 1/2" CL300	-	[6,10] 155,0		[5,63] 143	[4,50] 114,3	4 x 3/4-10 UNC
	[6,10] 155,0	-		[5,67] 144		
2" CL150	-	[6,18] 157,0		[6,02] 153	[4,75] 120,7	4 x 5/8-11 UNC
	[6,00] 152,4	-		[5,47] 139		
2" CL300	-	[6,50] 165		[5,63] 143	[5,00] 127	8 x 5/8-11 UNC
	[6,50] 165	-		[5,28] 134		
3" CL150	-	[7,52] 190,9		[5,00] 127	[6,00] 152,4	4 x 5/8-11 UNC
	[7,52] 190,9	-				THROUGH HOLE 4 x Ø19,1 [0,75]

This drawing includes confidential information which is the property of ASHCROFT INC. This copy is loaned for a specific purpose, with the understanding that it will not be reproduced or used for any other purpose or disclosed to others, and it will be returned on demand.

Dimensions in mm [inch]

General Dimension
P5500, NG160, Flange DN

Rev.	Description	Date	Na.	Date	Name
				27.09.16	J. Krott
				27.09.16	Th. Wal



DWG. NO.
B 076 | 1-P5500-NG160-Flange

All specifications are subject to change without notice.