



RANGE DN	$\phi D1$		$\phi G$	H3	$\phi K$	M
	$\geq 0,6$ bar	$\leq 400$ mbar				
DN20/PN40	[4,13] 105	[6,18] 157	[2,28] 58	[4,17] 106	[2,95] 75	4 x M12
DN25/PN40	[4,53] 115	[6,18] 157	[2,68] 68		[3,35] 85	
DN50/PN40	[6,50] 165	[6,50] 165	[4,02] 102	[2,00] 50,8	[4,92] 125	4 x M16
DN1" 150 lbs	[4,25] 108	-	[4,61] 117		[3,12] 79,2	4 x 1/2-13 UNC
DN1" 300 lbs	[4,88] 123,9	-	[4,57] 116	[4,80] 122	[3,50] 88,9	4 x 5/8-11 UNC
DN2" 150 lbs	[6,00] 152,4	-	[4,76] 121	[4,29] 109	[4,75] 120,7	
DN2" 300 lbs	[6,50] 165	-	[4,09] 104	[5,00] 127		8 x 5/8-11 UNC
DN3" 150 lbs	[7,52] 190,9	-	[3,63] 92,1	[4,29] 109	[6,00] 152,4	THROUGH HOLE 4 x $\phi$ 19,1
						4 x 5/8-11 UNC

This drawing includes confidential information which is the property of ASHCROFT INC. This copy is loaned for a specific purpose, with the understanding that it will not be reproduced or used for any other purpose or disclosed to others, and it will be returned on demand.

Rev.	Description	Date	Na.



Dimensions in mm [inch]

**General Dimension**  
**P6500, NG100, Flange DN**

DWG. NO.  
**B 076 | 1-P6500-NG100-Flange**

All specifications are subject to change without notice.