



RANGE DN	$\phi D1$		$\phi G$	H3	$\phi K$	M
	$\geq 0,6$ bar	$\leq 400$ mbar				
DN20/PN40	[4,13] 105	[6,18] 157	[2,28] 58	[5,35] 136	[2,95] 75	4 x M12
DN25/PN40	[4,53] 115	[6,18] 157	[2,68] 68		[3,35] 85	
DN50/PN40	[6,50] 165	[6,50] 165	[4,02] 102	[2,00] 50,8	[4,92] 125	4 x M16
DN1" 150 lbs	-	[4,25] 108	[2,00] 50,8		[5,75] 146	[3,12] 79,2
DN1" 300 lbs	[4,25] 108	-		[5,79] 147	[5,98] 152	[3,50] 88,9
DN2" 150 lbs	-	[4,88] 123,9	[3,63] 92,1	[5,94] 151	[4,75] 120,7	
DN2" 300 lbs	[6,00] 152,4	-		[6,02] 153	[5,63] 143	[5,00] 127
DN3" 150 lbs	[6,50] 165	-	[3,63] 92,1	[5,28] 134	[6,00] 152,4	THROUGH HOLE 4 x $\phi 19,1$
	-	[7,52] 190,9		[5,00] 127		[5,47] 139

This drawing includes confidential information which is the property of ASHCROFT INC. This copy is loaned for a specific purpose, with the understanding that it will not be reproduced or used for any other purpose or disclosed to others, and it will be returned on demand.

Rev.	Description	Date	Na.
A	Edited table	30.01.15	Krott



Dimensions in mm [inch]

**General Dimension**  
P6500, NG160, Flange DN

DWG. NO.  
B 076 | 1-P6500-NG160-Flange