


# G3 Pressure Transducer

## Features

- All-welded 316L stainless steel sensor and pressure connection
- Highly configurable; wide selection of pressure connections and electrical terminations
- Ranges vacuum to 5000 psi
- NSF-61 Compliant

## Typical Uses

- Performance vehicle racing
- Railroad/transportation
- Agriculture implements
- Compressor control
- HVAC and refrigeration
- Process automation and control
- Pump monitoring



**G3**  
Transducer

## Specifications

Reference Temperature:	72 °F ±2 °F (21 °C ±1 °C)
Accuracy Class (BFSL):	± 0.50% of span
Accuracy (TEB):	<b>±1.5% of Span:</b> From -20 to 85 °C (-4 to 185 °F) <b>±2.0% of Span:</b> From -40 to -20 °C (-40 to -4 °F) <b>±2.0% of Span:</b> From 85 to 125 °C (185 to 257 °F) Total Error Band Accuracy: includes the combined effects of non-linearity (Terminal Point Method), hysteresis, non-repeatability, temperature and zero offset and span setting errors
Stability:	≤ ±0.25% of span/year
Durability:	> 10 million cycles
Approvals:	NSF-61, CE/UKCA, CE, UL (UL 61010-1), (CSA 222 6101-1) UL Recognized component per UL-61010-1, CSA 22.2 6101-1 Electrical Equipment for Measurement, Control and Laboratory use

## Environmental Specifications

Temperature Limits:	Storage: -40 °F to 257 °F (-40 °C to +125 °C) Operating: -40 °F to 257 °F (-40 °C to +125 °C) Compensated: -40 °F to 257 °F (-40 °C to +125 °C)
Humidity Effects:	0 to 100% R.H., no effect

## Functional Specifications

Vibration Effects:	Random vibration (20 g) over temperature range (-40 °C to 125 °C)
Shock Effects:	100 gs, 6 ms
Drop Test:	Withstands 1 meter on concrete
Response Time:	<2 ms



Certified to NSF/ANSI CAN 61



## Key Benefits

- Broad temperature capability
- High EMI/RFI immunity ratings
- IP67 Ingress rating
- High performance ASIC based electronics

## Functional Specifications

Pressure Ranges:	Vacuum, compound, gauge 5 to 5000 psig and absolute 15 to 500 psia	
Warm-up Time:	> 500 msec	
Position Effect:	< ±0.01% span	
Overpressure:	Proof	Burst
≤200 psi	2X Range	5X Range
300 to 5000 psi	1.5X Range	3X Range

## Electrical Specifications

Reverse Polarity & Miswired Protected:	Yes
Insulation Breakdown Voltage:	100 Vac
Insulation Resistance:	>100 Mh @ 100 Vdc
Circuit Protection:	Reverse polarity and miswire protection

## Contact Us

1.800.328.8258  
ashcroft.com

All specifications are subject to change without notice. All sales subject to standard terms and conditions.

Ashcroft® and Trust the Shield® are trademarks of Ashcroft Inc. The following non-Ashcroft trademarks are the property of their respective owners: 17-4 PH®, AMP®, Deutsch®, Metri-Pack® and Superseal®.

For more information, see [Ashcroft Brands & Trademarks](#) ©2024 Ashcroft Inc. G3\_transducer\_ds\_RevE\_18-Nov-25

# G3 Pressure Transducer

## Output Signals Available

Voltage Output	Excitation	Supply Current
0-5 Vdc, 3 wire	9-36 Vdc	5 mA
0-10 Vdc, 3 wire	14-36 Vdc	5 mA
1-5 Vdc, 3 wire	9-36 Vdc	4 mA
1-6 Vdc, 3 wire	9-36 Vdc	4 mA
0.5-4.5 Vdc 3 wire	9-36 Vdc	4 mA
Ratiometric Output		
0.5-4.5 Vdc, 3 wire	5.0 Vdc +/- 0.5Vdc	3.5 mA
Current Output		
4-20 mA, 2 wire	9-36 Vdc	

## Environmental Rating

Rating	Electrical Connections
IP67, NEMA 4X	Metri-Pack®, Shielded cable, Flying leads Deutsch® DT & DTM, AMP® Superseal® and M12
IP65, NEMA 4X	Hirschmann® G, EN 175301-803 Form C (DIN 43650 C)

## Wetted Components

Diaphragm	316L Stainless Steel
Process Connection	316L Stainless Steel

## Non-Wetted Components


Housing	20% Glass Reinforced Nylon, Fire retardant to UL94 V1
---------	---

## Optional Features


Electrical Termination:	See Ordering Code
Process Connection Location:	See Ordering Code
Consult Factory For:	Pressure range options, Process connection locations, Approval descriptions

## Total Error Band (TEB)

Error limits of all points (0-100% of range)



## Power Supply & Load Resistance



# G3 Pressure Transducer

Ordering code	Example:	G37	M01	42	M2	60#	G	-	XTU
<b>Model</b>									
G37 - G3 Series, 1.5% Total Error Band -20 °C to 85 °C, 2.0% Total Error Band -40 °C to -20 °C and 85 °C to 125 °C		G37							
<b>Pressure Connection Size</b>									
M01 - 1/8 NPT - Male			M01						
M02 - 1/4 NPT - Male									
MEK - 7/16-20 SAE #4 - Male, not UL recognized over 10,000 psi range									
MEV - 9/16-18 SAE #6 Male w/Buna-N O-ring, not UL recognized over 10,000 psi range									
MS2 - 1/4-19 bsp - Male, not UL recognized over 10,000 psi range									
MG2 - G 1/4 B - Male									
M38 - 3/8-24 SAE #3 Male w/Buna-N O-ring									
M33 - 3/8-24 UNJF3A (w/37 ° cone seat)									
M76 - 7/16-20 UNJF3A (w/37 ° cone seat)									
<b>Output Signal</b>									
5 - 0-5 Vdc									
10 - 0-10 Vdc									
15 - 1-5 Vdc									
16 - 1-6 Vdc									
42 - 4-20 mA				42					
RM - 0.5-4.5 Vdc Ratio metric to 5 Vdc supply									
45 - 0.5 - 4.5 Vdc Ratio metric to 9-36 Vdc supply									
<b>Electrical Termination</b>									
<b>EN 175301-803 Form C (DIN 43650, Form C)</b>									
DC - No mating connector									
N1 - Mating connector, no cable									
N2 - Mating connector, 1 meter (3 feet) of cable									
N3 - Mating connector, 3 meter (10 feet) of cable									
N9 - Mating connector with customer specified length									
<b>M12 - Mates to Hirschmann® 933 172-100 or similar</b>									
EW - No mating connector									
E0 - W/mating connector, no cable									
E2 - W/mating connector, 1 meter (3 feet) of shielded cable									
E4 - W/mating connector, 3 meter (10 feet) of shielded cable									
E1 - W/mating connector, customer defined cable length									
<b>Pigtail - Shielded cable with PVC jacket and 24 AWG leads</b>									
F2 - W/1 meter (3 feet) cable length									
F3 - W/3 meter (10 feet) of cable length									
P1 - Customer specified length									
<b>Metri-Pack®</b>									
GN - No mating connection									
G2 - Mating connection with 1 meter (3 feet) of cable									
G3 - Mating connection with 3 meter (10 feet) of cable									
G1 - Mating connector with customer specified length									
<b>Hirschmann® G Series</b>									
HM - No mating connection									
M1 - W/mating connector, no cable									
M2 - Mating connection with 1 meter (3 feet) of cable					M2				
P9 - Mating connector with customer specified length									
<b>Flying Leads</b>									
W2 - 1 meter (3 feet) of flying leads									
W9 - Customer specified length									
<b>Deutsch® DT Series DT04-3P</b>									
DT - Without mating connector									
T2 - W/1 meter (3 feet) of cable									
T3 - W/3 meter (10 feet) of cable									
T1 - W/mating connector, customer specified length									
<b>Deutsch® DT Series DTM04-3P</b>									
DS- Without mating connector									
S2 - W/1 meter (3 feet) of cable									
S3 - W/3 meter (10 feet) of cable									
S1 - W/mating connector, customer specified length									
<b>AMP® Superseal®</b>									
AP - Without mating connector									
A2 - W/1 meter (3 feet) of cable									
A3 - W/3 meter (10 feet) of cable									
A1 - W/mating connector, customer specified length									
<b>Pressure Ranges (see range table on page 4)</b>									
60# - 60 psi						60#			
<b>Measurement Type</b>									
G - Gauge							G		
A - Absolute									
<b>Option (if including an option(s) must include an "X")</b>									
TU - Throttle Plug									X__ TU

# G3 Pressure Transducer


## G3 Range Table

	Range	Code	316SS	316SS ISO
Gauge	5 psi	5#		X
	15 psi	15#	X*	X
	30 psi	30#	X	X
	50 psi	50#	X	X
	60 psi	60#	X	X
	100 psi	100#	X	X
	150 psi	150#	X	X
	250 psi	250#	X	X
	300 psi	300#	X	X
	500 psi	500#	X	X
	750 psi	750#	X	X
	1,000 psi	1000#	X	X
	1,500 psi	1500#	X	X
	2,000 psi	2000#	X	X
	Compound	0 psi/-14.7 psi	0#&vac	X*
15 psi/-14.7 psi		15#&vac	X*	X
30 psi/-14.7 psi		30#&vac		X
60 psi/-14.7 psi		60#&vac		X
100 psi/-14.7 psi		100#&vac		X
150 psi/-14.7 psi		150#&vac		X
300 psi/-14.7 psi		300#&vac		X
Absolute	15 psi	15#		X
	30 psi	30#		X
	50 psi	50#		X
	60 psi	60#		X
	100 psi	100#		X
	250 psi	250#		X
	500 psi	500#		X

\*Not available with 4-20mA output

## Dimensions are identified in inches and [millimeters]

For reference only, consult Ashcroft for specific dimensional drawings.



\*Mates to Metri-Pack® Connector Body 12065286

\*\*Mates to Hirschmann® G4W1F Connector or Similar